MODEL FA840

ACTIVE GEAR® – model: FA840

Restraint lanyard – Rope adjuster, hook, carabiner and metal buckle – 1.3 m / 2.0 m

TECHNICAL DATA SHEET

ISSUE 2026-11-08 · EN

CATEGORY III · CE 2834

PERFORMANCE

EN 354:2010

Lanyard

≥ 25kN

Breaking strength

EN 358:2018

Work positioning belt

CE 2834 · CAT. III

Category III PPE — Regulation (EU) 2016/425 · read the user instructions

KEY FEATURES

- Designed to hold the user hands free in a stable work position
- Loop with thimbles for better durability
- High quality Alloy steel, heat treated
- Adjustable size from 1.3 to 2.0m
- Versatile connector

VARIANTS

Material	13MM twist rope, Alloy Steel scaffolding hook & carabiner
Length	1.3m / 2.0m
Gate opening	Scaffolding hooks 52MM (FA810), Carabiner 19MM (FA800)
Breaking Strength	>= 25kN
Weight	1 kg

PACKING

1 PIECE / BAG › 10 PIECES / CARTON

REFERENCES & LOGISTICS

HS code **5609 00 00 00** · Origin **China**

SKU	SIZE	EAN-13	CARTON L×W×H (M)	KG
FA840		7630048220622	0.35 × 0.25 × 0.25	10.60

Complies with Regulation (EU) 2016/425 — EU type-examination certificate CE-PC-240812-373-07-9A issued by CCQS Certification Services Limited (notified body 2834).

ISO 9001:2015
ISO 14001:2015
ISO 45001:2018

EU DECLARATION OF CONFORMITY

ACTIVE GEAR SA · Route de Chantemerle 58d · 1763 Granges-Paccot · Switzerland

sales@activegear.eu · www.activegear.eu

EU Authorised Representative: Active Gear Italia S.r.l., Via Cacciatori delle Alpi 1/A, 22070 Capiago Intimiano (CO), Italy